

C1222...12PP... | C1222...12PFC...


Ø 12mm, 行星齿轮系列 Planetary Gearbox Series

应用领域：医疗器械、安防设备、视像产品、高端智能电玩、个人保健产品等领域。

Applications: medical equipment, security systems and locks, audio and visual products, personal healthcare products, and high-end hobby products.

				C1222-95-2.5 -12PP120-0141	C1222-88-5.0 -12PP120-0142	C1222-80-2.5 -12PFC120-0228
电机参数 / Motor Data						
1	电压	Voltage	V	2.5	5.0	2.5
2	端电阻	Terminal resistance	Ω	3.5	17.8	5.3
3	空载转速	No-load speed	rpm	95	88	80
4	空载电流	No-load current	mA	60	35	50
5	最大转矩	Max torque	mNm	68.6	62.7	50
6	负载转矩	Load torque	mNm	14.7	14.7	15
7	负载转速	Load speed	rpm	75	66	56
8	负载电流	Load current	mA	180	100	185
9	减速比	Reduction ratio		1/120	1/120	1/120
10	重量	Weight	g	6.5	6.5	6.5
11	工作温度范围	Operating temperature range	°C	-10~+70	-10~+70	-10~+70
特性曲线 / Characteristics Curve						

C1222-95-2.5-12PP120-0141



仅供参考，详细了解请以产品规格书为准。
For reference only, please refer to the product specification.

可选配置 / Options

性能 Special coils: 连续运行范围内可定制 customizable in continuous operation rang

法兰 Flange: 标准前后法兰 standard front and rear flanges / 定制法兰 custom flanges

电气连接 Electrical connection: 端子或导线 connector or wire / 导线长度 lead wires length

外观图 / Outline Drawing

