


无感无刷电机通用驱动器 Universal ESC for Sensorless BLDC Motor

应用领域：风机、电动工具、泵类等领域。
Applications: blowers, electrical tools, pumps, etc.

				S17-112503	S17-114820
驱动器参数 / Driver Data					
1	持续电流	Constant current	A	3	20
2	峰值电流	Peak current(10s)	A	4.5	26
3	输入电压范围	Input voltage range	V	11~25	11~48
4	尺寸	Size	mm	99*72*25	99*72*25
5	速度控制信号	Speed control signal		Analog voltage/PWM	Analog voltage/PWM
6	过载保护	Overload protection		Yes	Yes
7	堵转保护	Blockage protection		Yes	Yes
8	过热保护	Thermal overload protection		Yes	Yes
9	反接保护	Inverse-polarity protection		Yes	Yes
10	正反转控制	CW/CCW direction control		Optional	Optional
11	使能控制	Enable		Optional	Optional
12	速度信号输出	Speed feedback output(6 pulses*pole pairs)		Optional	Optional
13	工作环境温度	Operating temperature	°C	-20~+60	-20~+60
14	换向方式	Sensorless or sensed		Sensorless	Sensorless

外观图 /Outline Drawing



M 1:2

型号 / Model S17-112503/S17-114820